

STYLUS PRO® COB

LITHIUM ION RECHARGEABLE AREA LIGHT

MARKET

APPLICATIONS: Professional Light - Hardware/Tool, Industrial, Law Enforcement, Security, Automotive, Sporting Goods, Consumer.

DESCRIPTION:

The Stylus Pro® COB is a sleek compact pen sized, USB rechargeable, lithium ion battery powered area light designed for use in all markets. It features a top switch for easy actuation of two lighting levels, a pocket clip for convenience, integrated magnet in tail cap, and amazing brightness and run time for a light of its size. The aluminum housing with Type II Military Spec anodizing helps make the light extremely durable and abrasion resistant. Packaged with a removable pocket clip. Available in Black.

CASE MATERIAL:

Machined aluminum alloy case. Type II MIL-Spec anodized finish.

DIMENSIONS:

Length: 6.64 in. (168.6 mm) Body Diameter: 0.55 in. (14.0 mm) Head diameter: .63" (16.0 mm)

WEIGHT:

2.2 oz. (62.4 grams) with battery.

LENS:

Polycarbonate lens; gasket sealed.

LIGHT SOURCE:

COB (chip on board) LED technology, impervious to shock with a 30,000 hour lifetime.

LIGHT OUTPUT:

High: 130 candela peak beam intensity, 23 meter beam distance and 160 lumens measured system output.



Low: 30 candela peak beam intensity, 11 meter beam distance and 40 lumens measured system output.

Fully regulated output for consistent lumen performance over the battery life.

ON/OFF:

Push button switch - constant on operation.

Press and hold button for 3 seconds to access flash mode. Press and hold again to go back to standard operation.

RUN TIME:


High: 3 hours of run time. Low: 8.5 hours of run time. Flash: 7 hours of run time. All runtime claims are to 10% of initial lumen output.

BATTERY:

Streamlight Lithium Ion cell pack with on board safety circuit. Rechargeable up to 300 times.

Fully recharges battery in 4.5 hours and charges battery in product.

Charge indication LED: Red - Charging; Green - Charged.

Red/Green on together, no battery in the light or bad battery.

FEATURES:


COB LED technology for extreme brightness.

IPX4 rated for water resistant operation. All openings O-ring sealed.

1 meter impact resistance tested.

Micro USB charge port under water resistant cover. Rechargeable using supplied USB cord.

Removable pocket clip.

Integrated magnet in tail cap.

APPROVALS:

CE Meets applicable European Community Directives.

BC CEC Compliant





WARRANTY:

Streamlight's Limited Lifetime Warranty

OPTIONAL
ACCESSORIES:

USB/AC adaptor(s)

OUTPUT

FL1 STANDARD	HIGH	LOW
	160 LUMENS	40 LUMENS
	3h	8.5h
	23m	11m
	130cd	30cd

RUNTIME
DISTANCE
INTENSITY
PERFORMANCE CURVE
