

## PRODUCT FACT SHEET

## ProTac® Rail Mount HL-X HIGH LUMEN RAIL MOUNTED STROBING TACTICAL LIGHT

**MARKET** 

**APPLICATIONS:** Law Enforcement, Security, Military, Home Defense

**DESCRIPTION:** Lightweight, compact, low profile, high lumen, lithium battery powered Gun-Mounted Tactical

Light featuring the latest in shock-proof power LED technology. It incorporates the versatility to use two battery types; two CR123A batteries, or one Streamlight Rechargeable Li Ion cell. The light provides 1 hour 20 minutes of continuous run time on high and over 20 hours on low intensity. Rail clamp designed to rapidly and securely attach/detach from rifles, carbines and submachine guns

with a MIL Standard 1913 Rail.

**CASE MATERIAL:** 6000 Series machined aircraft aluminum with Type II Mil-Spec anodized finish. Available in Black.

**DIMENSIONS:** Length: 5.43 in. (13.8 cm) Width: 1.45 in. (3.68 cm) Height: 1.72 in. (4.37 cm)

**WEIGHT:** 6.4 oz (181.4 grams) with CR123A batteries (included in purchase).

6.9 oz (195.6 grams) with optional 18650 Li Ion rechargeable battery. (not included in purchase)

**LENS:** High temperature, shock mounted, AR coated, impact resistant Boro Float glass.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: High: 27,600 candela peak beam intensity, 332m beam distance, 1000 lumens measured system

output.

Low: 1,600 candela peak beam intensity, 80m beam distance, 60 lumens measured system output.

Solid-state current regulation for consistent illumination level and the reflector produces a

concentrated beam with optimum peripheral illumination.

ON/OFF: Multi-function, push-button tactical tail switch or Dual remote pressure switch with latching push

button. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP®

programmable switch allows user selection of one of three different programs: high/strobe (factory

default), high only, or low/high.

**RUN TIME:** CR123A - High: One hour of regulated run time and one hour 20 minutes to 10% output.

Low: 18 hours of regulated run time and 20 hours to 10% output.

18650 - High: One hour 15 minutes of regulated run time and one and a half hours to 10% output.

Low: 22 hours of regulated run time and 23 hours to 10% output.

**BATTERY:** Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

One (1) Streamlight Li Ion 18650 protected cylindrical 3.7V 2600 mAh rechargeable battery that has

its own cradle charging system. (Optional)

**FEATURES:** C4<sup>®</sup>LED technology for extreme brightness.

Momentary/steady On-Off switch.

One handed on/off & tighten interface keeps hands away from muzzle when attaching/detaching.

Securely fits a broad range of weapons.

Mounts directly to guns with MIL-STD-1913 (Picatinny) rails. Extensively live-fire tested, impact resistant construction.

Operating temperature: -40°F to +120°F.

IPX7 rated with the Standard button switch installed; waterproof to 1 meter for 30 minutes.

IPX4 rated with the Remote Pressure Switch installed for water resistant operation.

APPROVALS: Meets applicable European Community Directives. ( )

**WARRANTY:** Streamlight's Limited Lifetime Warranty.

**OPTIONAL** 

ACCESSORIES: Red and Green Filters

Issued: 12/22/2016

Revised: Rev: Made in China Document #297